


Make: Promptec LED Lights Model: PAOL-101, 102, 103

Wattages: 10 to 50W







PAOL-102



PAOL-103



LM80 Certified



L70-70000 hrs.



Promptec LED Lights are the BEST model in its category in the World

- Saves 60 to 70% Energy when compared to conventional lights
- Highly optimized thermal design for guaranteed LED Life
- Available in A/C, D/C, Solar and hybrid models
- High Precision Constant Current LED driver (Greater than 90% Efficiency)
- Optimized electrical and thermal design to deliver life greater than 15 years.
- Integrated with industry leading LED's of 120 to 150 Lumen / Watt with LM80 Certifications
- Highly optimized Photometry to achieve greater than 80 Lm/Watt Efficacy with LM79 Certifications







- Corporate Offices
- Hospitals
- Government Offices
- IT campus
- Malls
- Library











PAOL-101

PAOL-102

PAOL-103

Product Specification*

ELECTRICAL

- Driver efficiency > 90%
- Voltage Harmonics < 2% (Allowed 10%)
- Current Harmonics < 5% (Allowed 15%)
- Power Factor >0.98 (Allowed 0.8)
- Over-heat, Over-voltage & Surge protections are provided.

PHOTOMETRY

- Efficacy: > 80 Lumen / Watt
- Secondary optics designed for office Lighting
- Meets IS standards of illumination
- LM80 certified LED for maximum life

LUMINARY

- Aluminum Die cast with Heat Sink grade aluminum
- Toughened glass with Silicon beading
- Best heat dissipation

Model: PAOL-101

Type: 2'x2' False Ceiling
Front View: 595x595 mm
Light area: 375x375 mm

Depth: 75 mm

Rear view: 575x575 mm Variants: PAOL-101-30W

> PAOL-101-40W PAOL-101-50W

Model: PAOL-102

Type: 1'x1' False Ceiling
Front View: 305x305 mm
Light area: 168x168 mm

Depth: 70 mm

Rear view: 280x280 mm Variants: PAOL-102-10W

> PAOL-102-15W PAOL-102-20W

Model: PAOL-103

Type: 2'x1' False Ceiling
Front View: 600x310 mm
Light area: 378x168 mm

Depth: 70 mm

Rear view: 572x282 mm
Variants: PAOL-103-20W

PAOL-103-30W